



POOLEX
Jetline®
SELECTION Fi

JETLINE SELECTION Fi

New generation Jetline

- Full Inverter technology
- Reversible
- Automatic defrosting
- Titanium Twisted Exchanger Tech
- Compatible with salt treatment

	75	95	125	155	210
Swimming pool volume	30-45m ³	40-50m ³	45-65m ³	65-80m ³	80-110m ³
cop air 26°C /water 26°C	6.2~13 ^{.6}	6.3~14	6.2~16 ^{.4}	6.1~16 ^{.3}	6.2~16 ^{.5}
Noise at 10m(db(a))	19~29	19~30	21~31	23~34	23~35

HEAT PUMP GUARANTEED 2 YEARS

COMPRESSOR GUARANTEED 5 YEARS

TITANIUM COIL GUARANTEED AGAINST CORROSION 15 YEARS



962 444 011

JETLINE SELECTION Fi		75	95	125	155	210
Pool volume		30 to 45m ³	40 to 50m ³	45 to 65m ³	65 to 80m ³	80 to 110m ³
Reference : PC-JLS		075N	095N	125N	155N	210N
Air 26°C Water 26°C Hygro 80%	Max. power output(kW)	7.1	9.05	11.9	15,3	20,1
	Min. power output (kW)	2.04	2.3	2.35	2.5	2.7
	Power consumption (kW)	1.15	1.51	1.92	2.51	3.24
	COP	6.2 ~ 13.6	6.3 ~ 14	6.2 ~ 16.4	6.1 ~ 16.3	6.2 ~ 16.5
Air 15°C Water 26°C Hygro 70%	Max. power output (kW)	5.4	6.7	8.7	10.9	14.6
	Min. power output (kW)	1.4	1.5	1.7	1.9	2.15
	Power consumption (kW)	1.15	1.49	1.89	2.37	3.17
	COP	4.7 ~ 6.5	4.5 ~ 6.6	4.6 ~ 7.8	4.6 ~ 7.7	4.6 ~ 7.9
Electricity supply		Mono 230V / 50Hz				
Heating temperature range		15°C / 40°C				
Operating range		-7°C / 43°C				
Max. power (kW)		1.38	1.83	2.62	2.9	4.2
Flow (m ³ /h)		2~4	3~4	4~6	5~7	7~9
Refrigerant		R32				
Dimensions (mm)		824x334x656			907x334x656	1104x354x756
Packaging dimensions (mm)		886x404x778			969x404x778	1166x424x878
Net / Gross weight (kg)		37,5 / 43,5		39,5 / 45,5	42,5 / 50	50,5 / 59
Noise level at 1 m (dB(A)) Inverter		37~50	37~51	38~52	40~54	41~55
Noise level at 10 m (dB(A)) Inverter		19~29	19~30	21~31	23~34	23~35
Compressor type		Hermetic Rotary DC Inverter				
Compressor brand		Mitsubishi				
Heat exchanger		Twisted Tech® Titanium				
Function		Auto / Boost / Eco / Heating / Cooling				

EU STANDARD TUV CERTIFIED
Data provided for information purposes only. Can be subject to change without notice.

Still as efficient, the new Poolex Jetline Selection Fi and its unmatched price/quality/efficiency ratio, remains a reference amongst swimming pools heat pumps.

With Full Inverter technology, this heat pump is able to vary the speed not only of its compressor, but also of its fan to adapt itself perfectly on demand, and thus effectively lower electricity consumption and acoustic pressure.

By virtue of its design and wide hydrophilic aluminium evaporation surface area, the Poolex Jetline Selection Fi operates at an outside temperature as low as -7°C.

With the new Twisted Tech® heat exchanger technology comprising of a titanium heating coil, the swimming pool's temperature is raised even more quickly.

Available in 5 output ratings from 7.1 to 20.1 kW, the Jetline Selection Fi is suitable for swimming pools up to 110 m³.

The POOLEX Advantage: All accessories included



Delivered on wooden pallet



Isothermal winter storage cover



Anti-vibration support kit



Ø 50mm 1 1/2 Connectors PVC



Wired control extension (10m)



Condensation drainage pipe



Maintenance kit including multi-language usermanual