Mergulho Salgado.pt Loja de Piscinas e Spas

INFLATABLE SPA



INFLATABLE SPA **MONTANA**

4 to 6 persons









Mergulho Salgado.pt Loja de Piscinas e Spas



INFLATABLE SPA

2 filtration cartridges included







Extra-comfortable seating 0.6 mm PVC with foam.



Secured & isothermal cover Laminated PVC with insulating aluminum sheet.



Ultra-resistant & designed structure
Unique design with leatherette finish.



Differential current 10 mA 100% safe against electrical hazards. Integrates a differential circuit breaker 10 mA.



Up to 140 air nozzles Perfect for a relaxing moment.



Smart Pump Unit Automatic temperature control function.

AFTER-SALES SERVICE

- Replacing pump in 72 hours.
- Assembly and disassembly in less than 5 minutes.
- Revolutionary system. The pump can be removed
- without emptying the spa.



MONTANA SPA

The benchmark in inflatable spas

Its original design turns it into a true **indoor and outdoor decorative feature.**

Designed with an **ultra-résistant laminated imitation leather PVC** outer layer and a **pearl** interior liner, the Montana spa combines technology and robustness.

Available in two sizes – **4 or 6 persons** – the Montana has an external motor unit for efficient filtering, an effective massage function and a **rapid and powerful heating system.**

heating system.		
Technical specifications		
Reference	SP-MTA135C	SP-MTA165C
Capacity	4 persons	6 persons
Interior/Exterior Liner	130 / 175 cm	160 / 204 cm
Height	70 cm	
Water level	44-47 cm	
Water volume	700 L	930 L
Air nozzles	110	140
Outer liner	Laminated and textured PVC	
Inner liner	Pearled PVC	
Ground protection	Synthetic fabric mat	
Cover	0.6 mm laminated PVC with aluminium sheet	
Straps	Secure locking with special buckles	
Control pannel	Integrated digital panel	
Power supply	240V~50Hz	
Pump	Air and bubble pump: 650 W	
	Air pump noise: 68 dB at 1 m	
	Filtration pump: 40 W	
	Filtration noise: 55 dB at 1 m	
	Filtration flow: 1200 L/h (320 gal/h)	
Heater	Power: 1500 W / 1.5°C - 2.5°C/hour	
	Maximum temperature: 42°C	
	Double heater isolation	
Usage conditions	5°C or above	
Certification	CE	